

# RUBBERWORX

## 300 PSI TEXTILE BRAID AIR



This heavy duty textile reinforced air hose with a pin pricked cover is specifically designed for use in compressed air service in industrial, construction, drilling and mining applications. The ozone and abrasion resistant cover holds up to the toughest applications.

<b>TUBE:</b>	SYNTHETIC NR/SBR BLEND
<b>REINFORCEMENT:</b>	2 HIGH-TENSILE BRAIDED TEXTILE
<b>COVER:</b>	YELLOW OZONE RESISTANT SYNTHETIC RUBBER
<b>TEMPERATURE:</b>	-22°F to 180°F
<b>BRANDING:</b>	300 PSI TEXTILE BRAID AIR
<b>PACKAGING SPECIFICATIONS:</b>	50', 100' COILS

SA #	ID (IN)	OD (IN)	WP (PSI)	BURST (PSI)	BEND RADIUS (IN)	VACUUM RATING (HG)	WEIGHT	PACKAGING
5005103-050	0.50	0.87	300	1200	NA	NA	0.22	50', 100'
5005103-063	0.63	0.98	300	1200	NA	NA	0.30	50', 100'
5005103-075	0.75	1.14	300	1200	NA	NA	0.38	50', 100'
5005103-100	1.00	1.42	300	1200	NA	NA	0.50	50', 100'
5005103-125	1.25	1.73	300	1200	NA	NA	0.61	50', 100'
5005103-150	1.50	2.01	300	1200	NA	NA	0.71	50', 100'
5005103-200	2.00	2.56	300	1200	NA	NA	1.15	50', 100'
5005103-250	2.50	3.15	300	1200	NA	NA	1.56	50', 100'
5005103-300	3.00	3.62	300	1200	NA	NA	1.95	50', 100'
5005103-400	4.00	4.65	300	1200	NA	NA	2.53	50', 100'